

Borderline Pulling Series (Points) 2019
Pro Farm (3x3)
9500-10,000
Must pass Tech inspection to participate

ALL GENERAL RULES APPLY!

Engine

- No RPM and speed limits.
- No larger than 466 cubic inch limit.
- Engine head must be OEM for that brand (no aftermarket heads).
- No overhead cams, 2 valves per cylinder.
- OEM intake and exhaust manifolds.
- Turbo: Maximum of a 3 inch inlet by 3 inch outlet. Must be smooth bore. No slots or slugs. No inner or after coolers.
- Water injection allowed in the crossover pipe and ported water is allowed in the intake manifold only, not the head.
- Diesel fuel only, no injection pump larger than a P-Pump.
- Must have cross bolts in exhaust pipe.
- All inline turbocharged engines are required to have one 3/8 inch thickness cable mounted between cylinders number 2-3 with 4 clamps at the splice, with no more than 4 inches of slack.

Safety

- SFI steel flywheel, SFI approved scatter blanket, wheelie bars, fenders, kill switch, 2.5 pound fire extinguisher, full roll cage with five point harness, side shields, air shutoff, full firewall. Must have a spring loaded throttle that returns to idle. Must have a 3 way dump valve ahead of the injection pump operated by a cable. Electric Fans are required.
- SFI approved fire suit, helmet, gloves and shoes.
- All competitors must sign notarized affidavit as proof of having a SFI steel flywheel.

Frame

- Block, driveline, transmission, rear axle and sheet metal must match the model of the manufacturer.
- Must have frame ties or a one piece frame.
- Maximum length of 13 feet from the center of the rear axle to the front of the tractor, including any type of weights.
- No tires larger than 20.8 x 38 cuts allowed. Aluminum rims allowed.